CACTUS TECHNOLOGIES

Secure Digital® microSD Card (SD) 803M Series





The Cactus Technologies Secure Digital microSD Card (SD) - 803M Series is a low capacity solid-state flash memory product that complies with the Secutre Digital Card Association (SDA) standard. Cactus microSD Cards provide up to 4GB (Class 6) of formatted storage capacity and are designed to be used in applications which require reliable, high performance solid state storage in a small form factor.

CACTUS MICROSD FEATURES

- INDUSTRY STANDARD MICROSD **CARD VERSION 1.1 AND 2.0**
- CARD CAPACITIES
 - 1GB to 4GB
- INTERFACE SUPPORTS
 - SD Interface
 - SPI Mode
- → VOLTAGE RANGE
 - 2.7V to 3.6V
- → TRACEABILITY ELECTRONIC CODE
- → SOLID STATE DESIGN WITH NO MOVING PARTS
- → INDUSTRY LEADING
 - Data Reliability
 - Shock & Vibration
 - Operating Temp Range
 - Data Transfer Rates
- ZERO DB NOISE
- → 4-MILLION HOUR MTBF
- → 5-YEAR WARRANTY



PERFORMANCE

Read Data Transfer Rate up to 20MB/sec

Write Data Transfer Rate up to 17MB/sec



RELIABILITY

- Supports Wear Leveling
- Error Checking & Correction
- Less Than 1 Error in 10¹⁴ Bits Read
- MTBF 4,000,000 Hours



ENVIRONMENTAL & POWER

Operating Temperature Range Standard -25°C to +85°C

Extended

-45°C to +90°C

POWER CONSUMPTION

 $3.3V \pm 10\%$ 60mA

Read Write 80mA Sleep 200uA



SHOCK & VIBRATION

Shock

Vibration 15G peak-to-peak

Secure Digital® microSD (SD) 803M Series





INDUSTRIAL GRADE MICROSD CARD

→ INTERFACE	SD Card Version 1.1 and Version 2.0	
→ INTERFACE TRANSFER RATE	25MB/sec	
→ POWER REQUIREMENT	DC Input Voltage	3.3V ± 10%
	Sleep	200uA
	Read	60mA
	Write	80mA
→ ENVIRONMENTAL SPECIFICATION	Standard Temperature	-25°C to +85°C
	Extended Temperature	-45°C to +90°C
	Humidity	8-95%, non-condensing
	Acoustic Noise	0dB
	Vibration	15G peak to peak max.
	Shock	50G max.
	Altitude	100,000 feet max.
→ RELIABILITY AND MAINTENANCE	Endurance	2,000,000 erase cycles per block
	MTBF	4,000,000 Hours
	Data Reliability	less than 1 Error in 10 ¹⁵ bits read
→ CARD CAPACITY	1GB to 4GB	

Cactus Technologies Limited

Suite C, 15/F, Capital Trade Center 62 Tsun Yip Street, Kwun Tong Kowloon, Hong Kong Tel: +852-2797-2277

Email: sales@cactus-tech.com

Cactus USA

3112 Windsor Road
Suite A356
Austin, Texas 78703
Tel: (512) 775-0746
Email: americas@cactus-tech.com



www.cactus-tech.com